

SCHNEIDER LABORATORIES

INCORPORATED

2512 W. Cary Street • Richmond, Virginia • 23220-5117
804-353-6778 • 800-785-LABS (5227) • (FAX) 804-359-1475

Excellence in Service and Technology

AIHA/ELLAP 100527, NVLAP 101150-0, NYELAP/NELAC 11413, CAELAP 2078, NC 593, SC 93003

LABORATORY ANALYSIS REPORT

Asbestos and Other Fibers Counted based on NIOSH 7400 Method, Issue 2, Aug. 12, 1994

Using SLI A8

ACCOUNT #:
CLIENT:
ADDRESS:

DATE COLLECTED: 7/28/2008
DATE RECEIVED: 8/19/2008
DATE ANALYZED: 8/26/2008
DATE REPORTED: 8/26/2008
RESPIRATOR: Half Face

PROJECT NAME:
JOB LOCATION:
PROJECT NO.:
PO NO.:

Personal and Excursion Samples Collected For OSHA Compliance.

SLI Sample No.	Client Sample No.	Sample Identification	Sample Date	Flow Rate (L/min)	Sample Time (min)	Sample Volume (L)	Fiber Count (f/field)	Actual Exp. (f/cc)	30 Min TWA (f/cc)	8 HR TWA (f/cc)
29860250	1Ex		7/28/2008	2.00	45	90.0	0.160	0.087	0.131	
29860251	2Per		7/28/2008	2.00	350	700.0	0.210	0.015		0.019

Analyst:

Total Number of Pages in Report: 1

Results relate only to samples as received by the laboratory.

Reviewed By:

Visit www.slabin.com for current certifications.

OSHA PELs are 1.0 f/cc for 30 min excursion and 0.1 f/cc for 8 hour TWA. Est. limit of detection: 7 f/mm² or 0.055 f/field. Data precision justifies 2 sig. figures. For f/mm², divide f/field by microscopic field area of 0.00785 mm². Results are not blank-corrected unless noted by analyst. Exposure calculations are based on client-supplied information and assume zero exposure for time not sampled. Est. relative standard deviations: Intra-Laboratory: ± 0.30; Inter-Laboratory: ± 0.38. Unusual sample conditions, if any, are described.