



Schneider Laboratories Global, Inc

2512 W. Cary Street • Richmond, Virginia • 23220-5117
804-353-6778 • 800-785-LABS (5227) • Fax 804-359-1475

Customer:

Address:

Order #: 120014

Matrix Air
Received 03/29/15
Analyzed 03/30/15
Reported 03/30/15

PO Number:

Attn:

Project:

Location:

Number:

Method NIOSH 7400 Issue 2 Aug. 12 1994

Sample ID	Cust. ID	Location	Date	Time	Vol.	Fibers (f/field)	Density (f/mm ²)	Exposure (f/cc)	30 Min TWA (f/cc)	8 Hr TWA (f/cc)
120014-001			03/29/15	30 min	60.0 L	<0.0550	<7.01	<0.0450		
120014-002			03/29/15	450 min	900 L	<0.0550	<7.01	<0.00300	<0.0450	
Aguilera, C.										<0.00562
120014-003			03/29/15	30 min	60.0 L	0.100	12.7	0.0817		
120014-004			03/29/15	450 min	900 L	<0.0550	<7.01	<0.00300	<0.0450	
Gaga, L.										<0.00792

Analyst: N/A

120014-03/30/15 02:32 PM

Analyst Sr

Initials	Range	Sr
N/A	5 - 20	0.0910
	20.5 - 50	0.0792
	50.5 - 100	0.0372

Reviewed By: _____

Personal and/or Excursion Samples. OSHA Asbestos PELs are 1.0 f/cc for 30 min excursion and 0.1 f/cc for 8 hour TWA. Est. limit of detection: 7 f/mm² or 0.055 f/field. (<) refers to less than limit of detection. Results are not blank-corrected unless noted by analyst. Exposure calculations are based on client-supplied information and assume zero exposure for time not sampled. Analyst relative standard deviation (Sr) calculated using historical data. Calculated values are reported to three significant figures.